

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

No. DoP-GB-Tilelt Ready-Mix Wall Adhesive-070219

1. *Unique identification code of the product-type:*
Tilelt Ready-Mix Wall Adhesive
2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*
Tilelt Ready-Mix Wall Adhesive (batch/production date/ production site is printed on packaging), dispersion tile adhesive class D1T.
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Internal tiling
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*
Saint-Gobain Construction Products UK Ltd. trading as Saint-Gobain Weber
Dickens House
Enterprise Way
Flitwick
Beds
MK45 5BY
UK

Web: www.uk.weber
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
Not applicable
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
AVCP system 3
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
EN 12004-1:2017
Lucideon, (1289)
performed Initial type testing under system 3
and issued Test report (184149)-34217/CR1
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
Not applicable

9. Declared performance

| Essential characteristics | Performance | Harmonized technical specification |
|--|---|------------------------------------|
| Initial shear adhesion strength | ≥1.0N/mm ² | EN 12004-2:2017, 8.4 |
| Shear adhesion strength after heat aging | ≥1.0N/mm ² | EN 12004-2:2017, 8.4 |
| Open time: tensile adhesion strength | ≥0.5 N/mm ² after not less than 20 minutes | EN 12004-2:2017, 8.1 |
| Slip | ≥0.5 mm | EN 12004-2:2017, 8.2 |
| Reaction to fire | E (CWFT) | EN 12004-1:2017, 4.4.3 |
| Release of dangerous substances | See safety data sheet | EN 12004-1:2017 |

NPD = No performance determined

CWFT = Classified Without Further Testing

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


LEO VAN BLOT

15/02/19.

 (place and date of issue)

HEAD OF TECHNICAL

 (name and function)



 (signature)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

1. (31) Safety data sheet: **MSDS (TileIt Ready-Mix Wall Adhesive)**
2. (33) Information on substances of very high concern: **Not applicable**