

DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

No. DoP-GB-Tilelt Ready-Mix Wall Adhesive Plus-070219

- 1. Unique identification code of the product-type: Tilelt Ready-Mix Wall Adhesive Plus
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): TileIt Ready-Mix Wall Adhesive Plus (batch/production date/ production site is printed on packaging), dispersion tile adhesive class D2TE.
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
 - Internal tiling
 - 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

Saint-Gobain Construction Products UK Ltd. trading as Saint-Gobain Weber

Dickens House Enterprise Way Flitwick Beds MK45 5BY UK

Web: www.uk.weber

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): Not applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: AVCP system 3
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 12004-1:2017 **Lucideon, (1289)** performed Initial type testing under system 3 and issued Test report (184152)-34224/CR1

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not applicable



9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Initial shear adhesion strength	≥1.0N/mm²	EN 12004-2:2017, 8.4
Shear adhesion strength after heat aging	≥1.0N/mm²	EN 12004-2:2017, 8.4
Extended open time: tensile adhesion strength	≥0.5 N/mm² after not less than 30 minutes	EN 12004-2:2017, 8.1
Slip	≥0.5 mm	EN 12004-2:2017, 8.2
Shear adhesion after water immersion	≥0.5 N/mm²	EN 12004-2:2017, 8.4
Shear adhesion at elevated temperature	≥1.0N/mm²	EN 12004-2:2017, 8.4
Reaction to fire	E (CWFT)	EN 12004-1:2017, 4.4.3
Release of dangerous substances	See safety data sheet	EN 12004-1:2017

NPD = No performance determined

CWFT = Classified Without Further Testing

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

LOG LAMBUST HEAD OF TECHNICION (name and function)

(place and date of issue)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

1. (31) Safety data sheet:

MSDS (Tilelt Ready-Mix Wall Adhesive Plus)

2. (33) Information on substances of very high concern: Not applicable