

## DECLARATION OF PERFORMANCE

in accordance with EU Construction Products Regulation (CPR) no 305/2011

### No. DoP-GB-fast set wall & floor tile adhesive-080617

1. *Unique identification code of the product-type:*  
**fast set wall & floor tile adhesive**
2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*  
**fast set wall & floor tile adhesive (batch/production date/ production site is printed on packaging)**
3. *Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
**All internal and external tiling**
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):*  
**Saint-Gobain Construction Products UK Limited trading as Saint-Gobain Weber**  
*Dickens House*  
*Enterprise Way*  
*Flitwick*  
*Beds*  
*MK45 5BY*  
*UK*  
  
Web: [www.netweber.co.uk](http://www.netweber.co.uk)
5. *Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
**Not applicable**
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
**AVCP system 3**
7. *In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
**EN 12004:2007+A1:2012**  
**CERAM, (1289)**  
*performed Initial type testing under system 3*  
*and issued Test report (124869)-20241*
8. *In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
**Not applicable**

## 9. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	E	EN 12004:2007+A1:2012
Release of dangerous substances	None	EN 12004:2007+A1:2012
Bond strength, as:		
Early tensile adhesion strength	$\geq 0.5 \text{N/mm}^2$	EN 12004:2007+A1:2012
Initial shear adhesion strength	$\geq 1.0 \text{N/mm}^2$	EN 12004:2007+A1:2012
Durability for:		
Tensile adhesion strength after heat ageing	$\geq 0.5 \text{N/mm}^2$	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion	$\geq 0.5 \text{N/mm}^2$	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze/thaw cycles	$\geq 0.5 \text{N/mm}^2$	EN 12004:2007+A1:2012


NPD = No performance determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:  
Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:

JAMES MEAD, TECHNICAL DIRECTOR  
(name and function)

FLITWICK, 08/06/17  
(place and date of issue)

  
(signature)

Attachments to DoP according to CPR Article 6 (5) and the REACH regulation (EC) No 1907/2006, Article 31 or Article 33

- (31) Safety data sheet: MSDS (fast set wall & floor tile adhesive)
- (33) Information on substances of very high concern: Not applicable